

# Fuseholders

For Low Voltage 3AG or SFE Fuse Applications

## RoHS Twist-Lock In-Line Type

### SPECIFICATIONS:

**Electrical:** Intended for use at 32 volts or less with fuses rated up to 20 amperes when the proper spring is installed for fuse size.

**Molded Parts:** Black Thermoplastic (UL 94V2). Body halves have a .14" diameter hole for insulated wire.

**Ambient Temperature:** -40°C to +75°C.

**Contact Rivet:** Brass. Tin finish. Designed to accommodate #14 AWG stranded wire.

**Assembled:** Includes fuse listed and 19" loop of #14 AWG red vinyl insulated wire.

**Unassembled:** For assembly to #14 AWG wire.


### OPTIONS:

150 215 is similar to 155 120A except no fuse is supplied. It is intended for use with 3AG fuses rated up to 20 amperes.

### UNIVERSAL IN-LINE FUSEHOLDER 155 100:

Supplied with 8" loop of #14 AWG red vinyl insulated wire and two springs in different lengths to accommodate SFE sized fuses.

\* Please refer to Fuseology section for information on proper fuseholder de-rating.



### ORDERING INFORMATION:

Unassembled		Assembled	
Catalog Number	For Fuse Size	Catalog Number	Fuse Installed
155 104U	1/4" x 5/8"	155 104A	SFE 4
155 106U	1/4" x 3/4"	155 106A	SFE 6
155 17.5U	1/4" x 7/8"	155 17.5A	SFE 7 1/2
155 109U	1/4" x 7/8"	155 109A	SFE 9
155 114U	1/4" x 1 1/16"	155 114A	SFE 14
155 120U	1/4" x 1 1/4"	155 120A	SFE 20

## RoHS Heavy-Duty Bayonet Knob In-Line Type

### SPECIFICATIONS:

**Electrical:** Intended for use at 32 volts or less with fuses rated up to 20 amperes when the proper spring is installed for full size.

**Molded Parts:** Body and knob are Black Thermoset (UL 94V0). Both body and knob have a .20" diameter hole for insulated wire.

**Knob:** Bayonet-lock type metal insert.

**Ambient Temperature:** -40°C to +125°C.

**Contact Rivet:** Brass. Tin plated. Designed to accommodate #14 AWG stranded wire.

**Assembled:** Includes fuse listed and 19" loop of #14 AWG red vinyl insulated wire.

**Unassembled:** For assembly to #14 AWG wire.

### OPTIONS:


150 079 is similar to 155 020A except no fuse is supplied. It is intended for use with 3AG fuses rated up to 20 amperes.

### UNIVERSAL IN-LINE FUSEHOLDER 150 145:

Supplied with 15" loop of #14 AWG red vinyl insulated wire and three springs in different lengths to accommodate SFE sized fuses.

Fuseholders with other wire sizes or lengths available on special order.

\* Please refer to Fuseology section for information on proper fuseholder de-rating.



### ORDERING INFORMATION:

Unassembled		Assembled	
Catalog Number	For Fuse Size	Catalog Number	Fuse Installed
155 004U	1/4" x 5/8"	155 004A	SFE 4
155 006U	1/4" x 3/4"	155 006A	SFE 6
155 07.5U	1/4" x 7/8"	155 07.5A	SFE 7 1/2
155 009U	1/4" x 7/8"	155 009A	SFE 9
155 014U	1/4" x 1 1/16"	155 014A	SFE 14
155 020U	1/4" x 1 1/4"	155 020A	SFE 20

## RoHS 2AG or 5 x 20mm Inline Fuseholders

### SPECIFICATIONS:

**Electrical:** This fuseholder, part number 150274, is intended for use with 2AG and 5 x 20mm fuses. Maximum current ratings are 5 amperes at 32V for the 2AG size fuses and 10 amperes at 32V for the 5 x 20mm size fuses.

**Body:** Black Thermoplastic.

**Terminals:** Brass.

**Wire:** 16 Awg size; nominal o.d. 0.104"; color red.

**Lead Pull Test:** Will withstand 10 lb. pull.

**Ambient Temperature:** -40°C to +80°C.

### ORDERING INFORMATION:

**Catalog Number:** 150 274

\* Please refer to Fuseology section for information on proper fuseholder de-rating.

